



Rvs schroeven met torxkop vullen het assortiment verzinkte verbindingmiddelen aan. Deze schroeven zijn geschikt voor corrosieve omgevingen en mogen alleen met rvs verbinders gebruikt worden.



[ETA-04/0013](#), [NL-DoP-e04/0013](#)

KENMERKEN



Materiaal


- Rvs AISI 316.

Inschroeven

- Met torx 20-bit.

Voordelen

- Dankzij de houtspecifieke schroefdraad wordt het dragermateriaal snel en eenvoudig ingesneden.



TOEPASSINGEN

Ondergrond



- **Drager / gedragen bouwdeel** : massief hout, composiethout, gelijmd gelamineerd hout.

Toepassingsgebieden

- Bevestigingen van ophangbeugels.
- Hoekijzers.
- Bandijzer.

TECHNISCHE GEGEVENS

Product dimensions and capacities



Referentie	Afmetingen bevestigingen [mm]					Karakteristieke waarden - Hout C24 overeenkomstig ETE-04/0013 [kN]	
	d	l	d _h	d ₁	l _g	R _{lat,k}	R _{ax,k}
CSA5,0X25S	4.85	25	8.3	3.15	19	1.49	1.38
CSA5,0X35S	4.85	35	8.3	3.15	29	1.99	2.11
CSA5,0X40S	4.85	40	8.3	3.15	34	2.25	2.47

Capacities are given for 2mm steel plate thickness and C24 timber. To determine the capacities for other steel thickness and / or timber grades, please refer to ETA-04/0013.

